

Datos técnicos		Unidades	Climate RAC 5000 2,6-2 R32	Climate RAC 5000 3,5-2 R32	Climate RAC 5000 5,3-2 R32	Climate RAC 5000 7,0-2 R32
Capacidad Frío	kW/h		2,6 (0,9 - 3,4)	3,5 (1,1 - 4,2)	5,3 (1,8 - 6,1)	7,0 (2,7 - 7,9)
	Kcal/h		2268 (756-2923)	3024 (958-3578)	4536 (1562-5267)	6048 (1789-6834)
Capacidad Calor	kW/h		2,9 (0,8 - 3,4)	3,8 (1,1 - 4,2)	5,6 (1,4 - 6,7)	7,3 (1,6 - 8,8)
	Kcal/h		2579 (688-3095)	3439 (757-3783)	4987 (963-5847)	6048 (2175-6535)
Consumo Frío	W		710 (100 - 1240)	1237 (130 - 1580)	1539 (140 - 2360)	2345 (160 - 2960)
Consumo Calor	W		739 (120 - 1200)	964 (100 - 1580)	1480 (200 - 2410)	2035 (260 - 3140)
Frío estacional	SEER (Etiqueta)	W/W	6,2 (A ^{**})	6,1 (A ^{**})	7,1 (A ^{**})	6,1 (A ^{**})
Calor (clima cálido /medio)	SCOP (Etiqueta)	W/W	4,9 (A ^{**})/4,0 (A [*])	4,6 (A ^{**})/4,0 (A [*])	5,2 (A ^{***})/4,0 (A [*])	5,0 (A ^{**})/4,0 (A [*])
Espectro ErP			A ^{***} →D	A ^{***} →D	A ^{***} →D	A ^{***} →D
Allimentación	V-Hz		220-240V-50Hz	220-240V-50Hz	220-240V-50Hz	220-240V-50Hz
Unidades interiores			Climate RAC 5000 2,6-3 IBW	Climate RAC 5000 3,5-3 IBW	Climate RAC 5000 5,3-3 IBW	Climate RAC 5000 7-3 IBW
Nivel de presión sonora (Si/Bajo/Medio/Alto)	dB(A)		21/26/30/40	22/26/34/40	25/30/37/44	28/35/42/45
Dimensiones (Ancho x Profundo x Alto)	mm		805x194x285	805x194x285	957x213x302	1040x220x327
Peso Neto/Bruto	Kg		7,6/9,7	7,6/9,7	10,0/13,0	12,3/15,8
Unidades exteriores			Climate RAC 5000 2,6-2 OUE	Climate RAC 5000 3,5-2 OUE	Climate RAC 5000 5,3-2 OUE	Climate RAC 5000 7-2 OUE
Caudal de aire	m3/h		1700	1700	2500	3000
Nivel de presión sonora	dB(A)		56	56	56	60
Dimensiones (Ancho x Profundo x Alto)	mm		700x275x550	700x275x550	800x333x554	845x363x702
Peso Neto/Bruto	Kg		22,8/25,2	22,7/25,2	34,0/36,7	51,5/54,5
Refrigerante	Tipo		R32	R32	R32	R32
	GWP		675	675	675	675
	Cantidad carga	Kg	0,5	0,5	1,0	1,6
	Equivalente de CO ₂	Ton	0,338	0,338	0,675	1,080
	Distancia estándar	m	5	5	5	5
	Carga adicional	g/m	12	12	12	24
Tubería refrigerante	Líquido / Gas	pulg.	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"	3/8"-5/8"
	Máx. Longitud	m	25	25	30	50
	Máx. Vertical	m	10	10	20	25

(1) Precio base de venta. IVA no incluido.
 Contiene gas refrigerante R32 con GWP = 675.